



SwimPro EXP



SwimPro™ TOP-MOUNT SAND FILTERS

Hayward SwimPro high-rate sand filters offer superb spherical pool filter technology with smooth, efficient flow and totally balanced backwashing.

SwimPro sand filters feature single piece construction of both main tank body and integral base with corrosion-proof, polymeric material. The internal design features a durable innovative under drain assembly that ensures balanced flow. A versatile seven-position control valve offers both easy operation and maximum efficiency.

For crystal clear, sparkling water with minimum care, SwimPro filters set the standard for performance, value and dependability.

FILTERS

SPECIFICATIONS - SwimPro™ HIGH-RATE SAND FILTERS

Filter Type	High-Rate Sand ½ Silica Sand (.45 mm - .55mm), Zeolite or Glass
Filter Tank	Moulded Polymeric
Underdrain	Full Flow innovative box design for Balanced Flow
Control Valve	40mm 7-Position, Top-Mount Vari-Flo™ with Lever-Action Handle
Valve Fastening	Flange Clamp Design
Support Base	Integral with Filter Body



Vari-Flo™ 7-Position Control Valve with easy-to-use lever-action handle lets you “dial” any of seven valve/filter functions.

PERFORMANCE DATA

MODEL	EFFECTIVE FILTERATIONS AREA	DESIGN FLOW RATE	DESIGN FLOWRATE	MAX WORKING PREASURE	REQ		TYPE	AMOUNT
					SIDE	ABOVE		
170 EXP	1,5 FT ²	25 GPM/FT ²	38 GPM	50 PSI	18"	18"	45 mm - 55 mm SILICA SAND	100 LB 45 KG
	0,14 M ²	1017 LPM/M ²	144 LPM	3,4 BAR	46 CM	46 CM		
190 EXP	1,8 FT ²	25 GPM/FT ²	45 GPM	50 PSI	18"	18"	45 mm - 55 mm SILICA SAND	175 LB 79 KG
	0,17 M ²	1017 LPM/M ²	170 LPM	3,4 BAR	46 CM	46 CM		
230 EXP	2,7 FT ²	20 GPM/FT ²	54 GPM	50 PSI	18"	18"	45 mm - 55 mm SILICA SAND	250 LB 114 KG
	0,25 M ²	814 LPM/M ²	204 LPM	3,4 BAR	46 CM	46 CM		
270 EXP	3,7 FT ²	20 GPM/FT ²	74 GPM	50 PSI	18"	18"	45 mm - 55 mm SILICA SAND	350 LB 160 KG
	0,35 M ²	814 LPM/M ²	280 LPM	3,4 BAR	46 CM	46 CM		
311 EXP	4,95 FT ²	20 GPM/FT ²	99 GPM	50 PSI	18"	18"	45 mm - 55 mm SILICA SAND	350 LB 160 KG
	0,46 M ²	814 LPM/M ²	375 LPM	3,4 BAR	46 CM	46 CM		